
UNO & DUPLO

FOLDING WALLS

ESPERO



Uno & Duplo walls can be finished with practically all materials customarily used in interiors. Almost unlimited creative possibilities are offered by the choice from, for example, high quality melamine, hard plastic laminate, vinyl, paint and veneers which are stitched, glued and lacquered in Espero's own factory. The combination of white Uno walls with the multi-coloured chairs at Tempus in Schiedam provide a fresh and modern interior that can flexibly and easily partitioned.

UNO & DUPLO



1 two Uno wings that close in the middle

2 door handle with Euro-cylinderlock



UNO & DUPLO

The panels in a Uno or Duplo wall are always stacked in line with the main track and it is possible to open and close the wall at one side, in the middle or at both ends. It is also possible to connect several walls on to each other. The combination of sturdy construction and high-quality materials provides years of trouble-free use.



positioning examples



KUNSTENCENTRUM SNEEK (NL)




3 simple and effective partitioning of two treatment cubicles

4 flexible rubber sweep seal at the top and bottom (option with Uno wall)




one-sided closure



centre closure



closure on both sides



centre and side closure

ESPERO

UNO & DUPLO

Key features and advantages:

- quick and easy to operate
- wide choice of finishes

- suitable for intensive use
- ultra-efficient low-cost wall-system

Option:

- curved ceiling rails



5 a Duplo wall functionally integrated in modern architecture

6 a Duplo wall with centre closure, sufficient privacy thanks to the sound insulation rating of ± 43 dB.




LAB. VOOR INFECTIEZIEKTEN GRONINGEN (NL)

UNO&DUPLO



TYPE	UNO	DUPLO
Use	In gemiddelde tot grotere ruimten.	
Dimensions:		
Panel width	196 mm	192 mm
Panel height	maximum 3,300 mm	maximum 4,000 mm
Package width	225 mm	444 mm
Wing length	max. 6,500 mm	max. 6,500 mm
Package depth in storage*	70 mm per metre wall width + 120 mm/closure post	150 mm per meter wall width + 150 mm end post + 150 mm closure post
	* Calculated dimensions are approximate, exact sizes are available on request.	
Wall / opening width	Wall widths are unlimited when using multiple wings.	
Alcove width	350 mm	500 mm
Material	High-grade EI quality chipboard 12 mm.	
Finishing	All common materials used in interior finishing can be used.	
Hinges	Extruded PVC profile in black, white or grey.	
Sound insulation rating (approximately)	28 dB	41 dB, 43 dB
Weight	20 kg/m ²	40 kg/m ² , 41 kg/m ²
Top and bottom sealing	Flexible sweep seal at top and bottom.	
Closure	The end panel is always a closure post. The closure post connects to an aluminium wall jamb and is fitted with an aluminium T-handle that operates the hook lock	
Lock	Euro-cylinder (length 90 mm)	Euro-cylinder (length 90 mm)
Track	Hard aluminium profile, technically anodised colourless, 42x32 mm (w x h).	
Wheels / trolleys	Bearing-mounted with wear-resistant plastic running surfaces that ensure the panels move silently and smoothly.	
Pellets + track	242 x 32 mm (w x h)	350 x 32 mm (w x h)
Static behaviour	The panels are top-hung in the track and must not be subjected to any external loads.	
Environmental conditions	Only suitable for indoor applications. Maximum relative humidity 60%.	

Other specifications available on request. Espero reserves the right to make changes without prior notification. For the most recent version, go to: www.espero.nl



Espero prioritises customer satisfaction. The production process, modern advanced machinery, the product quality, the expertise and professionalism of our employees; everything has been designed to live up to and, wherever possible, to exceed the expectations of our customers.

By maintaining frequent and intensive contact with clients and suppliers, we can quickly and flexibly respond to new wishes and requirements with innovative products. Our employees work in a pleasant and safe environment in the office, in the factory and on the road. They receive the right support to encourage their personal development and take (additional) training courses in order to guarantee the high quality and excellent service for which Espero is known now and in the future.

ESPERO

ESPERO

MOBILE WALLS



Enquire about our FSC certified products.

visiting adress

Espero BV
Sluisweg 26 - 28
5145 PE Waalwijk
The Netherlands

postal adress

Espero BV
Postbus 576
5140 AN Waalwijk
The Netherlands

t +31 (0)416 338955
f +31 (0)416 332635
e info@espero.nl
i www.espero.nl

Ask for the documentation for more information about our other wall systems: Sonico, Visio 100, Visio and Uno&Duplo. Espero is the exclusive agent for Skyfold full automatic vertical wall systems in the Netherlands.

